

(19) World Intellectual Property Organization  
International Bureau




(43) International Publication Date  
2 October 2003 (02.10.2003)

PCT

(10) International Publication Number  
**WO 03/081882 A1**

- (51) International Patent Classification<sup>7</sup>: **H04M 1/73, H04Q 7/32**
- (21) International Application Number: **PCT/FI03/00222**
- (22) International Filing Date: **24 March 2003 (24.03.2003)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:  
20020570                      25 March 2002 (25.03.2002)    **FI**
- (71) Applicant (*for all designated States except US*): **NOKIA CORPORATION [FI/FI]; Keilalahdentie 4, FIN-02150 Espoo (FI).**
- (72) Inventors; and
- (75) Inventors/Applicants (*for US only*): **SORVARI, Antti [FI/FI]; Landbontie 35, FIN-01100 Itäsalmi (FI). KÄHÄRI, Markus [FI/FI]; Metsäpurontie 20 C 21, FIN-00630 Helsinki (FI).**
- (74) Agent: **BERGGREN OY AB; P. O. Box 16, Jaakonkatu 3 A, FIN-00101 Helsinki (FI).**
- (81) Designated States (*national*): **AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.**
- (84) Designated States (*regional*): **ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).**
- Published:**  
— *with international search report*
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: **DISTRIBUTION OF TASKS OVER TIME IN A MOBILE TERMINAL**



(57) Abstract: The invention relates to a method, a device and a process for distributing various tasks performed by a mobile terminal (101) over time. The idea of the invention is to increase talk and standby times of said terminal (101) by executing as many power consuming, delayable tasks as possible when the terminal is connected to a charging device (102). Advanced solution exploits e.g. ideal task execution time intervals, the calculation of which is based on gathered user profile information. An intelligent charging device (102) with memory and processing means to share the task execution with said terminal (101) or to completely take care of some tasks on behalf of said terminal (101) is presented.



**WO 03/081882 A1**

4/PRTS

1

10/509008

PCT/FI03/00222

DT09 Rec'd PCT/PTO 24 SEP 2004

## Distribution of tasks over time in a mobile terminal

The invention relates to a method, a device and a process for distributing various tasks performed by a mobile terminal over time.

- 5 One current concern is the power consumption of the mobile terminals, which with new features related to mobile Internet and 3G technology require more power. Other issues to consider are the network capacity, cost and QoS (Quality of Service) demands which vary depending on time and the nature of the required service.

10 There are a few known solutions relating to the flexible downloading of data or retrieving and sending e.g. electronic mail by a mobile terminal. US Patents 5 896 566 and 5 689 825 disclose the use of a battery charger module with built-in connection to a PLMN (Public Land Mobile Network) network. The availability of a software update is detected by the mobile terminal, and the update is downloaded via the charger using the quality and speed of a fixed line network, when the  
15 terminal is placed in the charger. However, this solution is due to the rather costly and complicated dual connection viable only where the bandwidth over the air interface available is narrow, making the transfer of large data files slow, and when the signal quality is low resulting high error rates.

20 The Nokia 9110i (trademarks of Nokia Corporation), which is a handset with email and other data communication facilities, has an in-built feature for timed fetching of mails or information from the Internet, like webpages. However, no powersaving or cost-saving considerations are made.

25 In the third generation mobile terminals including UMTS (Universal Mobile Telecommunication System) terminals, there is functionality and capacity for sufficiently error-free and quick downloading of data files over the air interface, making the mobile terminals to this respect essentially comparable with devices connected to PLMN networks. At the same time the usage will require longer and longer talk and standby times. By developing better batteries and more efficient power management the terminal's power performance can be stretched further.  
30 However, as can be envisaged by the advent of mobile Internet browsing, frequent downloads of music or video files require that all solutions that can decrease the power consumption of these mobile terminals should be investigated.

In order to overcome the problems mentioned above, the present invention discloses a method, a device and a process for distributing various tasks performed by a mobile terminal over time, with the idea to minimize the need for battery power of mobile terminals in performing certain tasks and functions. A basic assumption in this context is, that as the complexity of the mobile terminals increases it is apparent that there will be several power consuming operations wherein the exact time of execution is not very critical. It is also possible to identify the tasks which are, for some reason or another, to be performed by advanced mobile terminals more favourably at some time later on instead of instantly.

10 According to the invention, a method for determining the time of execution for tasks to be performed by a mobile wireless communications terminal, wherein said execution is postponed to a later point of time, is characterized in that said method comprises the steps of

- 15 - receiving in the mobile terminal instructions to perform one or more tasks that can be executed with a delay,
- storing said instructions in a queue,
- checking in said terminal whether said terminal is coupled to a charging device,
- executing said tasks upon recognising an electrical connection between said mobile terminal and said charging device.

20

In another aspect of the invention, a method for determining the time of execution for tasks to be performed by a mobile wireless communications terminal, where said execution is postponed to a later point of time, is characterized in that said method comprises the steps of

- 25 - studying under a period of time the battery charging routines of the user,
- calculating time intervals with a high likelihood that said mobile terminal is being connected to the charger,
- receiving in the mobile terminal instructions to perform one or more tasks that can be executed with a delay,
- 30 - storing the instructions in a queue,
- executing said tasks upon entering one of said calculated time intervals.

In a further aspect of the invention, a method for determining the time of execution for tasks to be performed by a mobile wireless communications terminal, where said execution is postponed to a later point of time, is characterized in that said method comprises the steps of

35

- studying under a period of time the battery charging routines of the user,
- calculating time intervals with a high likelihood said mobile terminal being connected to the charger,
- receiving in the mobile terminal instructions to perform one or more tasks that can be executed with a delay,
- 5 - storing the instructions in a queue to be executed during said time interval,
- checking in the mobile terminal whether said mobile terminal is coupled to a charging device upon entering said time interval, executing said tasks if that is the case;
- 10 - deferring the execution of said tasks in said time interval, if the mobile terminal is not coupled to a charging device, until one of the following conditions applies, whichever occurs first:
  - the mobile terminal is connected to a charging device;
  - the maximum time limit for postponing the execution of said tasks is approaching;
  - 15 - the level of battery power available is approaching a limit putting execution of at least part of said postponed tasks at risk.

20 In a further aspect of the invention, a mobile wireless communications terminal capable of wireless speech and data communication over an air interface, said terminal including processing means for processing tasks and timing means for performing timed execution of said tasks, said terminal including memory means for storing instructions and data associated with each such task, is characterized in that said terminal is arranged to store received instructions for delayable tasks in a queue  
25 located in the memory, wait until coupled to a charging device and then execute said tasks.

In a further aspect of the invention, a mobile wireless communications terminal capable of wireless speech and data communication over an air interface, said terminal including processing means for processing tasks and timing means for  
30 performing timed execution of said tasks, memory means for storing instructions and data associated with each such task, data transmission means for data connection between said terminal and said charging device, is characterized in that said terminal is arranged to transfer at least part of the data to be processed in said instructions to said charging device for storage, and arranged to retrieve said stored  
35 data during said task execution.

In a further aspect of the invention, a mobile wireless communications terminal capable of wireless speech and data communication over an air interface, said terminal including processing means for processing tasks and timing means for performing timed execution of said tasks, memory means for storing instructions and data associated with each such task, is characterized in that said processing means of said terminal are arranged to study under a period of time the battery charging routines of the user, calculate the time intervals with a high likelihood that said terminal is being connected to the charger and execute the instructions stored in the memory to perform one or more delayable tasks upon entering one of said calculated time intervals.

In a further aspect of the invention, a mobile wireless communications terminal capable of wireless speech and data communication over an air interface, said terminal including processing means for processing tasks and timing means for performing timed execution of said tasks, memory means for storing instructions and data associated with each such task, is characterized in that said terminal is arranged to study under a period of time the battery charging routines of the user, calculate time intervals with a high likelihood the mobile terminal being connected to the charger, receive in the mobile terminal instructions to perform one or more tasks that can be executed with a delay, store the instructions in a queue located in the memory, check in said terminal whether it is coupled to a charging device, execute said tasks if that is the case or defer the execution of said tasks in said time interval, if the mobile terminal is not coupled to a charging device, until one of the following conditions applies, whichever occurs first:

- the mobile terminal is connected to a charging device;
- the maximum time limit for postponing the execution of said tasks is approaching;
- the level of battery power available is approaching a limit putting execution of at least part of said postponed tasks at risk.

In a further aspect of the invention, a charging device capable of charging the battery of a mobile wireless communications terminal, said charging device including data transmission means for a two-way data connection between said charging device and a mobile wireless communications terminal, said charging device including memory means for storing data, is characterized in that said charging device is arranged to store at least part of the data to be processed in the instructions associated with tasks to be executed by said terminal, and arranged to return said stored data to said mobile terminal when requested by said terminal.

In a further aspect of the invention, a charging device capable of charging the battery of a mobile wireless communications terminal, said charging device including data transmission means for a two-way data connection between said charging device and a mobile wireless communications terminal, said charging device including memory means for storing data, is characterized in that said charging device comprises processing means for the task execution sharing between said terminal and said charging device.

In a further aspect of the invention, a process for delayed execution of tasks in a mobile wireless communications terminal capable of wireless speech and data communication over an air interface, said terminal including processing means for processing tasks and timing means for performing timed execution of said tasks, said terminal including memory means for storing instructions and data associated with each such task, is characterized in that said process comprises the steps wherein

- said mobile terminal receives at least one instruction to perform a task,
- said terminal identifies the task as a delayable background task,
- said terminal stores the data related to the execution of delayable task in a queue located in the memory,
- said terminal executes said task using the processing means of said terminal upon recognising a connection between the battery of said terminal and the power source of a charging device.

In a further aspect of the invention, a process for delayed execution of tasks in a mobile wireless communications terminal capable of wireless speech and data communication over an air interface, said terminal including processing means for processing tasks and timing means for performing timed execution of said tasks, said terminal including memory means for storing instructions and data associated with each such task, is characterized in that said process comprises the steps wherein

- said mobile terminal receives at least one instruction to perform a task,
- said terminal identifies the task as a delayable background task,
- said terminal stores the data related to the execution of delayable task in a queue located in the memory,
- said terminal executes said task using the processing unit upon entering the precalculated time interval based on studying the battery charging routines of the user during which said terminal is being connected to a charging device.

Examples of delayable background operations could be:

- downloading and prefetching (precaching) of content such as Internet pages, music, games, photographs
- calculation of user profiles and preferences related to personalization and recommendation applications
- periodical virus scanning
- compression of files to save memory or disk space/flash memory
- organization of stored files to prevent fragmentation of files which in turn saves power and speeds up the terminal.

- 10 In executing as many battery power consuming operations as possible when the terminal is being connected to a battery charger, the standby time of the battery and the working time for other functions, like talking, displaying and playback, can in practice be significantly increased.

- 15 In one embodiment of the invention the terminal could be set up to learn the habits of the user and utilize the learned information to automatically schedule the execution of power consuming background activities. The terminal may or may not to have to communicate with the mobile network or services. The desired tasks may be executed whether or not the terminal is connected to the charger, but under otherwise favourable conditions, e.g. during the night, when bandwidth is available
- 20 at lower rates and the terminal has learnt that the user usually leaves the terminal with the battery fully charged for the night.

- In another embodiment of the invention, the performance of background operations is shared with an "intelligent" charging unit. In this case the charging unit would make it possible to reduce the processing power, memory and communication
- 25 capacity requirements of the mobile terminal.

In the following, the invention is described in more detail by reference to the attached drawings, wherein

- fig. 1 shows a mobile terminal (101) inserted in a battery charger (102),
- fig. 2 is a block diagram of the terminal (101) and the battery charger (102),
- 30 fig. 3 is a chart disclosing a first embodiment of the invention,
- fig. 4 is a chart disclosing a second embodiment of the invention,
- fig. 5 is a chart disclosing a third embodiment of the invention.

Referring to figures 1 and 2, the basic elements involved in the inventive concept are a mobile terminal (101) including components like a transceiver (204), a processing unit with timer capabilities (203), a program/data memory (201) and an user interface (202), and a charging device (102) adapted to receive the terminal, make connection to battery connectors thereof and thus being able to recharge the battery (205) or batteries of said terminal (101). In addition to mandatory power source (207), an "intelligent" charger could include a memory (209) or even a processing unit (210) to temporarily store or process the information transmitted from the terminal (101) using a two-way data connection (206,208) between the terminal (101) and the charger (102). Usually, the charger (102) is connected to a domestic or car power outlet (not shown).

In this first embodiment of the invention, the charging device (102) does not differ from the devices already on the market; the only function it has is to recharge the batteries of the mobile terminal (101). The features of this embodiment will be explained in more detail below, including embodiments incorporating learning and utilising the charging behaviour of the user.

The mobile terminal (101) is equipped, among other things, with music playback functionality, and the user has ordered a music data file to be delivered to the mobile terminal (101) via the Internet. The music file format can, for example, be the popular MP3 format, or any other format the mobile terminal is capable to handle. The amount of power required for receiving an MP3 music file is quite high. As approximately 1 MB of data is required for each minute of music, the user of the mobile terminal (101) is, according to the present invention, inclined to download the music while the terminal (101) is being connected to a battery charger (102), in order to optimise the processing of power consuming background operations. Also, as the user has no time or desire to listen to this particular piece of music immediately, he has ordered the file to be delivered to the mobile terminal (101), say within the next 24 hours. This deferred downloading is referred to as background downloading.

According to the flowchart of figure 3, the inventive process is initiated by the user who issues an audio file download order (301). The mobile terminal (101) checks whether immediate or background downloading is requested by the user (302). Let us assume that the user has a default maximum time for the background download of 24 hours. In this case no specific time is given, and the terminal (101) identifies the command as a default background download command, and assumes normal operation while pushing the download task in its command stack or similar queue of



tasks located in the memory (201) to be performed later on (303) by the processing unit (203), when the terminal (101) is connected to a battery charger (102). Additionally, if the user tends to abort the charging phase before completion due to his irregular lifestyle etc., it may be advantageous to defer the task execution until  
5 the battery (102) is fully charged. Anyway, the operations can be taken from the queue by following e.g. first-in-first-out (FIFO) principle, or by a predetermined priority. Stacking commands and operands are within the normal skills of any system programmer, so this function as such needs not to be explained in more detail.

10 According to the flowchart of figure 4, in the second embodiment of the present invention, the mobile terminal (101) has analyzed the battery charging routines of the user and calculated favourable time intervals to execute background tasks (401). During those intervals the terminal (101) is most probably being connected to a charger (102). After receiving instructions to perform a task without specified  
15 execution time (402), the terminal (101) defers the task execution until the calculated time interval is entered (403). Typically, tasks like this involve downloading and prefetching (precaching) of content such as Internet pages, music, games, photographs, and the mobile terminal (101) requests the service ( or a separate content delivery system) to send e.g. an MP3 music file between 1-6 a.m.,  
20 since during this time said terminal (101) is usually connected to a charger (102) and the battery (205) is full. When the user wants to have the music file ready in the morning, the downloading is performed before the specified time limit. Other types of tasks involving merely internal calculation (see below) may in these cases be less prioritised, and execution of them is postponed until all data transfer requiring tasks  
25 have been executed.

In such an embodiment, based on user behaviour monitoring and if any additional decision rules are not considered, the delayable task may be performed during the calculated time interval whether the mobile terminal (101) is connected to the charging device (102) or not, thus running the risk of consuming extra battery power  
30 every now and then. However, as the device learns the behaviour of the user, and the user learns to know the details of this feature, the occurrence of these cases where downloading or background processing is made without power backup from the charger may in practise be rare, without any consequences in power failures.

In the third embodiment of the present invention, see the flowchart of figure 5, the  
35 terminal (101) also exploits the calculated time intervals (501) for determining the proper execution time of delayable tasks (502). In addition, the terminal (101) may

decide to wait during said calculated time interval (503) until said terminal actually is connected (504) to a charging device (102), and extending this waiting time until the end of the time delay available, or until the level of battery power available is approaching a limit putting the full execution of the queued tasks at risk. There may be more options how to handle those situations, of course, some of which may be user-determined, e.g. by issuing a task priority list (505). For example, if the terminal (101) is coupled to a charger (102) in late evening, a fair assumption would be that it will stay there for the rest of the night. In a simple implementation, the terminal (101) sends the request for delivery immediately, or when the battery (205) is fully charged. In another implementation, the terminal (101) may wait till the expected traffic conditions and data transfer costs are optimal, e.g. until midnight. To be able to optimise the utilization of favourable traffic conditions and data transfer costs, the terminal (101) may have to communicate with the service provider and network carrier. By using slower connection speeds or channels than would be possible at instant downloading and listening, in a period of quiet traffic, normal daytime services can be achieved at significantly lower costs. There are tasks requiring lots of calculation but little or no data transfer over the air interface. Such tasks are, for example, calculation of user profiles and preferences related to compression of files to save memory or disk space/flash memory; and organization of stored files to prevent fragmentation of files which in turn saves power and speeds up the terminal. In such cases, the benefits are mostly due to the power saving aspect of the invention, requiring the terminal (101) actually being coupled to the charger (102).

An example of a learning rule that could initiate a more intelligent timing of the queued tasks would be, for example: IF the user with 95% probability fully charges the terminal's battery every night, AND there is on the average minimum six hours of charging & battery full time, THEN trigger the intelligent cost-saving mode.

In another aspect of the invention, the charging device (102) is equipped with circuitry making it possible for it to share processing tasks with the mobile terminal (101), or to completely execute certain tasks on behalf of the mobile terminal (101) while said terminal is inserted in the charging unit (102).

Further embodiments of the invention include sharing task execution between the mobile terminal (101) and the charging device (102). In such cases the charger (102) includes functionalities on top of merely battery charging, and should most probably be custom built for the mobile terminal. In one embodiment of the invention, the charging device (102) is provided with an additional memory capacity (209),

making it possible to background download more data than would fit into the mobile terminal (101) itself. Data can then be swapped or copied between the mobile terminal (101) and the charging device (102) in a similar fashion as it is done e.g. between the device memory and the SIM (Secure Identity Module) card module in today's GSM (Global System for Mobile Communications) cellular phones.

In another embodiment, the charging device (102) is provided with processing power of its own (210), making it possible for it to perform tasks where the mobile terminal (101) only needs to collect the raw data, send it to the charging device (102) and receive the end results of the executed tasks. Performing memory- and energy consuming, not time critical tasks inside the mobile terminal (101) gives no added value to the user in the cases of e.g. calculating of user profiles and preferences related to personalization and recommendation applications, periodical virus scanning, compression of files to save memory or disk space/flash memory, and organization of stored files to prevent fragmentation of files which in turn saves power and speeds up the terminal.

Some of the background tasks may be only user-initiated, but many of them may be part of pre-programmed service and maintenance routines, being thus self-initiated and scheduled by the system. Of course a manual and overruling initiation of any background task by the user should be possible, e.g. an instant virus scanning.

Implementations of some of aforesaid embodiments require a data connection (206,208) between the mobile terminal (101) and the charging device (102), and an appropriate protocol and software to control the process. Today's mobile terminals are, however, increasingly well equipped with standardized platforms to handle data exchange with other devices, such as personal computers, sensors, pointing devices etc. Such platforms include wireless infrared- and LPRF (e.g. Bluetooth) based Personal Area Network (PAN) solutions, and wired connections to computers, FM radios, external keyboards and the like. It is thus for one skilled in the art not difficult to implement a suitable data transfer solution between a charging device (102) and a mobile terminal (101), as most new mobile terminal models already have a suitable capability in-built.

According to the invention, having an intelligent charging device provided with a processor and memory of its own, can in most cases of normal usage considerably relieve the processing tasks of e.g. forthcoming third generation mobile terminals. This makes it possible apart from saving battery power and cost to reduce memory and processing power requirements of the mobile terminals, making them even more

less energy consuming, thus prolonging standby and active usage times. The mobile terminal can also be made lighter and smaller, the obvious other side of the coin would be to direct the available extra power saved to top-notch video and multi-media applications.

**Claims**

1. A method for determining the time of execution for tasks to be performed by a mobile wireless communications terminal (101), wherein said execution is postponed to a later point of time, **characterized** in that said method comprises the steps of
- 5       - receiving in the mobile terminal (101) instructions (301) to perform one or more tasks that can be executed with a delay (302),  
      - storing said instructions in a queue,  
      - checking (303) in said terminal (101) whether said terminal (101) is  
10       coupled to a charging device (102),  
      - executing said tasks upon recognising an electrical connection between said mobile terminal (101) and said charging device (102).
2. A method according to claim 1, **characterized** wherein the step of receiving instructions includes receiving instructions from the user via the user interface (202)  
15       of said mobile terminal (101).
3. A method according to claim 1 or 2, **characterized** wherein the step of receiving instructions includes receiving instructions generated internally in said mobile terminal (101) triggered by a maintenance or update process.
4. A method according to claim 1, **characterized** wherein the method further  
20       includes the steps of transferring at least part of the data to be processed in said instructions to said charging device (102) for storage (209), and retrieving said data during said step of executing said tasks.
5. A method according to claim 1, **characterized** wherein the method further  
25       includes the steps of transferring at least part of the data to be processed in said instructions to said charging device (102) for storage (209) and processing (210), and retrieving processed data from said charging device (102) during said step of executing said tasks.
6. A method for determining the time of execution for tasks to be performed by a mobile wireless communications terminal (101), where said execution is postponed  
30       to a later point of time, **characterized** in that said method comprises the steps of  
      - studying under a period of time the battery charging routines of the user,  
      - calculating time intervals (401) with a high likelihood that said mobile terminal (101) is being connected to the charger (102),

- receiving in the mobile terminal instructions to perform one or more tasks that can be executed with a delay (402),
- storing the instructions in a queue,
- executing said tasks upon entering one of said calculated time intervals (403).

7. A method according to claim 6, characterized wherein the step of receiving instructions include receiving instructions from the user via the user interface (202) of said mobile terminal (101).
8. A method according to claim 6 or 7, characterized wherein the step of receiving instructions includes receiving instructions generated internally in said mobile terminal (101) triggered by a maintenance or update process.
9. A method according to claim 6, characterized wherein the step of executing said tasks in said time interval is made using a connection speed and/or communications channel providing at least the minimum accepted Quality of Service (QoS) at the lowest possible cost.
10. A method according to claim 6, characterized wherein the step of executing said tasks in said time intervals involves the additional step of checking if the mobile terminal (101) is coupled to a battery charging device (102), and concluding according to a predetermined set of rules whether to start executing any queued tasks or not.
11. A method for determining the time of execution for tasks to be performed by a mobile wireless communications terminal (101), where said execution is postponed to a later point of time, characterized in that said method comprises the steps of
- studying under a period of time the battery charging routines of the user,
  - calculating time intervals (501) with a high likelihood said mobile terminal (101) being connected to the charger (102),
  - receiving in the mobile terminal instructions to perform one or more tasks that can be executed with a delay (502),
  - storing the instructions in a queue to be executed during said time interval (503),
  - checking (504) in the mobile terminal (101) whether said mobile terminal is coupled to a charging device (102) upon entering said time interval, executing said tasks if that is the case;

- deferring the execution of said tasks in said time interval, if the mobile terminal (101) is not coupled to a charging device (102), until one of the following conditions applies (505), whichever occurs first:

- 5           - the mobile terminal (101) is connected to a charging device (102);
- the maximum time limit for postponing the execution of said tasks is approaching;
- the level of battery power available is approaching a limit putting execution of at least part of said postponed tasks at risk.

10   12. A mobile wireless communications terminal (101) capable of wireless speech and data communication over an air interface (204), said terminal (101) including processing means for processing tasks and timing means for performing timed execution of said tasks (203), said terminal (101) including memory means for storing instructions and data associated with each such task (201), characterized in  
15   that said terminal (101) is arranged to store received instructions for delayable tasks in a queue located in the memory (201), wait until coupled to a charging device (102) and then execute said tasks.

13. A mobile wireless communications terminal according to claim 12, characterized wherein at least part of the stored instructions for delayable tasks are  
20   originally received from the user via the user interface (202) of said terminal.

14. A mobile wireless communications terminal according to claim 12, characterized wherein at least part of the stored instructions for delayable tasks are generated by an internal maintenance or update process (201) of said terminal (101).

15. A mobile wireless communications terminal (101) capable of wireless speech  
25   and data communication over an air interface (204), said terminal including processing means for processing tasks and timing means for performing timed execution of said tasks (203), memory means for storing instructions and data associated with each such task (201), data transmission means (206) for data connection between said terminal (101) and said charging device (102),  
30   characterized in that said terminal (101) is arranged to transfer at least part of the data to be processed in said instructions to said charging device (102) for storage (209), and arranged to retrieve said stored data during said task execution.

16. A mobile wireless communication terminal according to claim 15, characterized in that it is arranged to transfer at least part of the data to be

processed in said instructions to said charging device (102) for processing (210), and arranged to retrieve processed data during said task execution.

17. A mobile wireless communications terminal (101) capable of wireless speech and data communication over an air interface (204), said terminal including  
5 processing means for processing tasks and timing means for performing timed execution of said tasks (203), memory means for storing instructions and data associated with each such task (201), **characterized** in that said processing means (203) of said terminal (101) are arranged to study under a period of time the battery charging routines of the user, calculate the time intervals with a high likelihood that  
10 said terminal (101) is being connected to the charger (102) and execute the instructions stored in the memory (201) to perform one or more delayable tasks upon entering one of said calculated time intervals.

18. A mobile wireless communications terminal according to claim 17,  
15 **characterized** in that said processing means (203) are arranged to execute said tasks in said time interval using a connection speed and/or communications channel providing at least the minimum accepted Quality of Service (QoS) at the lowest possible cost.

19. A mobile wireless communications terminal according to claim 17,  
20 **characterized** in that said processing means (203) are arranged to check during said execution phase if said mobile terminal (101) is coupled to a battery charging device (102), and conclude according to a predetermined set of rules whether to start executing any queued task or not.

20. A mobile wireless communications terminal according to claim 18,  
25 **characterized** in that it is arranged to communicate with the service provider and/or network carrier for enabling the utilization of favourable traffic conditions and transfer costs.

21. A mobile wireless communications terminal (101) capable of wireless speech and data communication over an air interface (204), said terminal including  
30 processing means for processing tasks and timing means for performing timed execution of said tasks (203), memory means for storing instructions and data associated with each such task (201), **characterized** in that said terminal (101) is arranged to study under a period of time the battery charging routines of the user, calculate time intervals with a high likelihood the mobile terminal (101) being  
35 connected to the charger (102), receive in the mobile terminal (101) instructions to



perform one or more tasks that can be executed with a delay, store the instructions in a queue (201) located in the memory (201), check in said terminal whether it is coupled to a charging device(102), execute said tasks if that is the case or defer the execution of said tasks in said time interval, if the mobile terminal (101) is not  
5 coupled to a charging device (102), until one of the following conditions applies, whichever occurs first:

- the mobile terminal (101) is connected to a charging device (102);
- the maximum time limit for postponing the execution of said tasks is approaching;
- 10 - the level of battery power available is approaching a limit putting execution of at least part of said postponed tasks at risk.

22. A mobile wireless communications terminal according to claim 12,17 or 21, characterized in that it is substantially an UMTS terminal.

23. A charging device (102) capable of charging the battery (205) of a mobile  
15 wireless communications terminal (101) , said charging device (102) including data transmission means (208) for a two-way data connection between said charging device (102) and a mobile wireless communications terminal (101), said charging device (102) including memory means for storing data (209), characterized in that  
20 said charging device (102) is arranged to store at least part of the data to be processed in the instructions associated with tasks to be executed by said terminal (101), and arranged to return said stored data to said mobile terminal (101) when requested by said terminal (101).

24. A charging device (102) capable of charging the battery (205) of a mobile wireless communications terminal (101) , said charging device (102) including data  
25 transmission means (208) for a two-way data connection between said charging device (102) and a mobile wireless communications terminal (101), said charging device (102) including memory means for storing data (209), characterized in that said charging device (102) comprises processing means (210) for the task execution sharing between said terminal (101) and said charging device (102).

30 25. A charging device according to claim 24, characterized in that it comprises processing means (210) for the task execution on behalf of said terminal (101).

26. A process for delayed execution of tasks in a mobile wireless communications terminal (101) capable of wireless speech and data communication over an air interface (204), said terminal including processing means for processing tasks and

timing means for performing timed execution of said tasks (203), said terminal including memory means for storing instructions and data associated with each such task (201), characterized in that said process comprises the steps wherein

- 5       - said mobile terminal (101) receives at least one instruction to perform a task (301),
- said terminal (101) identifies the task as a delayable background task (302),
- said terminal (101) stores the data related to the execution of delayable task in a queue located in the memory (201),
- 10       - said terminal (101) executes said task (303) using the processing means (203) of said terminal (101) upon recognising a connection between the battery (205) of said terminal (101) and the power source (207) of a charging device (102).

27. A process according to claim 26, characterized in that said received  
15 instructions for delayable tasks are received from the user via the user interface (202) of said terminal (101).

28. A process according to claim 26, characterized in that said received  
instructions for delayable tasks are generated internally in said mobile terminal (101), triggered by a maintenance or update process stored in the memory (201) and  
20 executed in the processing unit (203).

29. A process according to claim 26, characterized in that the information for said identification of delayable tasks is included in said received instructions.

30. A process according to claim 26, characterized in that the information for said identification of delayable tasks is found from a predetermined list of task  
25 urgencies stored in the memory of said terminal (201).

31. A process for delayed execution of tasks in a mobile wireless communications terminal (101) capable of wireless speech and data communication over an air interface (204), said terminal including processing means for processing tasks and timing means for performing timed execution of said tasks (203), said terminal  
30 including memory means for storing instructions and data associated with each such task (201), characterized in that said process comprises the steps wherein

- said mobile terminal (101) receives at least one instruction to perform a task (401),

- said terminal (101) identifies the task as a delayable background task (402),
  - said terminal (101) stores the data related to the execution of delayable task in a queue located in the memory (201),
  - 5 - said terminal (101) executes said task using the processing unit (203) upon entering the precalculated time interval (403) based on studying the battery charging routines of the user during which said terminal (101) is being connected to a charging device (102).
32. A process according to claim 31, characterized in that said terminal (101)
- 10 checks during said time interval and prior to said task execution if said terminal (101) is coupled to a charging device (102), and decides according to a pre-determined set of rules whether to start executing said tasks or not.




Fig.1




Fig.2

2/4




Fig.3

3/4




Fig.4




Fig.5

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 03/00222

## A. CLASSIFICATION OF SUBJECT MATTER

IPC7: H04M 1/73, H04Q 7/32

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: H04M, H04Q, H02J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPI EPODOC

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 1032230 A2 (SONY CORPORATION), 25 February 2000 (25.02.00), page 2, line 8 - line 24; page 6, line 22 - line 30, claim 1, abstract  --	1-32
A	US 5689825 A (ZIVA AVERBUCH ET AL), 18 November 1997 (18.11.97), column 2, line 10 - line 36, abstract  --	1-32
A	US 5896566 A (ZIVA AVERBUCH ET AL), 20 April 1999 (20.04.99), column 2, line 19 - line 34, claim 1, abstract  --	1-32

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

\* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&amp;" document member of the same patent family

Date of the actual completion of the international search

23 May 2003

Date of mailing of the international search report

06-06-2003

Name and mailing address of the ISA/  
Swedish Patent Office  
Box 5055, S-102 42 STOCKHOLM  
Facsimile No. +46 8 666 02 86

Authorized officer

Tomas Wässingbo /mj  
Telephone No. +46 8 782 25 00



## INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 03/00222

## C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 6344727 B1 (DIPITI DESAI ET AL), 5 February 2002 (05.02.02), column 2, line 11 - line 38, claim 1, abstract  --	1-32
A	US 2001055978 A1 (ALAN HERROD ET AL), 27 December 2001 (27.12.01), abstract, see paragraph [0074] - [0077]  -- -----	1-32

**INTERNATIONAL SEARCH REPORT**  
Information on patent family members

29/04/03

International application No.  
PCT/FI 03/00222

Patent document cited in search report			Publication date	Patent family member(s)		Publication date
EP	1032230	A2	25/02/00	CN	1266345 A	13/09/00
				JP	2000253010 A	14/09/00
				US	6229990 B	08/05/01
-----						
US	5689825	A	18/11/97	NONE		
-----						
US	5896566	A	20/04/99	NONE		
-----						
US	6344727	B1	05/02/02	NONE		
-----						
US	2001055978	A1	27/12/01	US	6405049 B	11/06/02
-----						